



INNOSTAVIA YMPÄRISTÖJÄ
TIETEELLE JA TUTKIMUKSELLE

VISU Easy

Lightweight protection

Lightweight, high-pressure laminate surfaced VISU Easy table hood is suited for light working or to protect a device, for example.

- The hood can be placed on a worktop and can be equipped with a worktop and base.
- Available with or without a front sash.
- The lightweight hood's exhaust air connection is at the top, and it is connected to machinery air conditioning.
- The hoods are always equipped according to the customer's needs. Our experts will be happy to help you find suitable solutions.



Product information

Standard widths	600, 900, 1200 and 1500 mm
Working area depth	526 or 726 mm.
Total depth	600 or 800 mm.
Total height	1231 mm without glass hatch.
Materials of sides and back wall	High-pressure laminate-coated, humidity-resistant chipboard.
Front wall	Vertical or diagonal glass hatch made of clear polycarbonate or laminated glass.
By order	Worktop, base, under-desk cabinets, sockets.

Additional technical information

The technical properties depend on the hood width.

VISU KALUSTE OY

📍 Eeliksentie 6, 34870 Visuvesi, Finland

✉️ visu@visu.fi

☎️ +358 44 749 4940

🌐 visu.fi




INNOSTAVIA YMPÄRISTÖJÄ
TIETEELLE JA TUTKIMUKSELLE

Standard widths, [mm]	600	900	1200	1500	
Interior width, [mm]	562	862	1162	1462	Depending on side materials.
Air volume, [l/s]	35-70	54-108	73-145	92-183	Sash 250 mm open, 0.25-0.5 m/s air flow.
Ventilation connection, [mm]	160	160	200	200	


Delivery and installation

Safety cabinets are delivered, if so agreed, installed in place, ready to be connected to building technology systems. A safety cabinet must be connected to a separate exhaust air duct. Any water supply, drainage, gas and electricity work must be performed by professionals.

VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi