



INNOSTAVIA YMPÄRISTÖJÄ  
TIETEELLE JA TUTKIMUKSELLE

## VISU Easy

### Lightweight protection

Lightweight, high-pressure laminate surfaced VISU Easy table hood is suited for light working or to protect a device, for example.

- The hood can be placed on a worktop and can be equipped with a worktop and base.
- Available with or without a front sash.
- The lightweight hood's exhaust air connection is at the top, and it is connected to machinery air conditioning.
- The hoods are always equipped according to the customer's needs. Our experts will be happy to help you find suitable solutions.



### Product information

<b>Standard widths</b>	600, 900, 1200 and 1500 mm
<b>Working area depth</b>	526 or 726 mm.
<b>Total depth</b>	600 or 800 mm.
<b>Total height</b>	1231 mm without glass hatch.
<b>Materials of sides and back wall</b>	High-pressure laminate-coated, humidity-resistant chipboard.
<b>By order</b>	Vertical or diagonal sash. Made of clear polycarbonate or laminated glass, varies by width.* Worktop, base, under-desk cabinets, sockets.

\*More information in the Additional technical information tab.

### Additional technical information

The technical properties depend on the hood width.

### VISU KALUSTE OY

📍 Eeliksentie 6, 34870 Visuvesi, Finland

✉️ visu@visu.fi

☎️ +358 44 749 4940

🌐 visu.fi




INNOSTAVIA YMPÄRISTÖJÄ  
TIETEELLE JA TUTKIMUKSELLE

Standard widths, [mm]	600	900	1200	1500	
Interior width, [mm]	562	862	1162	1462	Depending on side materials.
Air volume, [l/s]	35-70	54-108	73-145	92-183	Sash 250 mm open, 0.25-0.5 m/s air flow.
Ventilation connection, [mm]	160	160	200	200	
Sash material	PC	glass	glass	glass	

## Delivery and installation

Safety cabinets are delivered, if so agreed, installed in place, ready to be connected to building technology systems. A safety cabinet must be connected to a separate exhaust air duct. Any water supply, drainage, gas and electricity work must be performed by professionals.

### VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi