

OPPILab Teach Pro

Movable teaching fume cupboard for more demanding use


- A movable fume cupboard, for example, to follow a teacher's demonstration.
- All walls of the fume cupboard are transparent safety glass.
- Suction takes place from the top and from the base surface along the entire width.
- The height can be adjusted manually or electrically.
- The worktop material is acidproof steel or ceramic.
- Equipped with LED lights and sockets for greater usability.
- The fume cupboard has an optimally designed front edge, continuous handle and side profiles to optimize air flow.



Product information

Standard width	900 and 1200 mm.
Worktop depth	600 mm
Total depth	806 mm
Total height	1-part glass opened 2645 mm (can be reduced). With the sash lowered, 2230 mm.
Worktop material	Acidproof steel or ceramic.
Materials of sides and back wall	Transparent safety glass.

VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi



INNOSTAVIA YMPÄRISTÖJÄ
TIETEELLE JA TUTKIMUKSELLE


Front wall	Vertical laminated safety glass.
Height adjustment	Manual 850–1000 mm (Pro), electrically adjustable 760–1000 mm (Premium).
Sockets	IP21, 4 pcs as standard, 5m power cord + plug.
Air conditioning	0-1 IC switch or automatic IC control option.

Additional technical information


The technical properties depend on the fume hood width.

Standard widths, [mm]	900	1200	
Air volume, [l/s]	125	170	The sash 300 mm open, 0.5 m/s inflow.
Standard lights, led W (lumen)	10/(1040)	15(1521)	
Ventilation connection, [mm]	200	200	2m flexible AC exhaust pipe with D200 quick connect couplings.
Castors	D100	D100	Two fixed, and two turning and lockable.

VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi