

## OPPILab Teach Pro

Movable teaching fume cupboard for more demanding use


- A movable fume cupboard, for example, to follow a teacher's demonstration.
- All walls of the fume cupboard are transparent safety glass.
- Suction takes place from the top and from the base surface along the entire width.
- The height can be adjusted manually or electrically.
- The worktop material is acidproof steel or ceramic.
- Equipped with LED lights and sockets for greater usability.
- The fume cupboard has an optimally designed front edge, continuous handle and side profiles to optimize air flow.




### Product information

<b>Standard width</b>	900 and 1200 mm
<b>Worktop depth</b>	600 mm
<b>Total depth</b>	806 mm
<b>Total height</b>	1-part glass opened 2645 mm (can be reduced). With the sash lowered, 2230 mm.
<b>Worktop material</b>	Acidproof steel or ceramic.
<b>Materials of sides and back wall</b>	Transparent safety glass.
<b>Front wall</b>	Vertical laminated safety glass.
<b>Height adjustment</b>	Manual 850–1000 mm (Pro), electrically adjustable 760–1000 mm (Premium).
<b>Sockets</b>	IP21, 4 pcs as standard, 5m power cord + plug.

### VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi



INNOSTAVIA YMPÄRISTÖJÄ  
TIETEELLE JA TUTKIMUKSELLE

#### Air conditioning


0-1 IC switch or automatic IC control option.

### Additional technical information


The technical properties depend on the fume hood width.

<b>Standard widths [mm]</b>	900	1200	
<b>Air volume [l/s]</b>	125	170	The sash 300 mm open, 0.5 m/s inflow.
<b>Standard lights LED [W] (lumen)</b>	10 (1040)	15 (1521)	
<b>Ventilation connection [mm]</b>	200	200	2m flexible AC exhaust pipe with D200 quick connect couplings.
<b>Castors</b>	D100	D100	Two fixed, and two turning and lockable.

#### VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi