

L-desk

With manual height adjustment

- The worktop material is acid- and chemical-resistant solid laminate (T2). Other options are also available; read more on the [Worktop materials](#) page.
- The recessed front leg improves seated ergonomics when multiple desks are positioned side by side.
- Manual height adjustment
- The streamlined design ensures easy cleanability.
- Under-desk cabinets are attached to the table frame, leaving floor space free and allowing the cabinet to be repositioned under the work surface. The cabinet can also be relocated to another desk.
- Our standard solutions feature the most commonly used dimensions.
- Custom solutions are always tailored to the customer's needs.



Standard


Description	Product code	Standard dimensions [mm]			Additional information
		Width	Depth	Height	
L-desk	RL-T2	400 - 2,300*	600, 700**, 800	700 - 900	
L-desk	RLp-T2	500 - 2,300*	600, 700**, 800	840 - 1,040	On casters
L-desk	RL-AH-T2	400 - 2,300*	600, 700**, 800	700 - 900	With full size lower shelf
L-desk	RLp-AH-T2	500 - 2,300*	600, 700**, 800	840 - 1,040	On casters & with full size lower shelf
L-corner desk	RL-K-T2	1,280 - 2,300*	1,280 - 2,300*	700 - 900	Worktop depth 600 or 800 mm, specified in the order. Note: The worktop will have a seam if required by its size.

* Widths available in 100 mm increments.

** In tables with a depth of 700 mm, a 100 mm deep free space remains for building services (e.g., utilities).

Custom

VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi



INNOSTAVIA YMPÄRISTÖJÄ
TIETEELLE JA TUTKIMUKSELLE

In addition to the standard models, we also manufacture desks according to client specifications. In the custom solutions, dimensions, materials, and features are entirely up to the client.

Feel free to ask our experts for more information, and let's design the right solutions together!

Additional information

Installation method	Free-standing on the floor, adjustable feet as standard. Note: desks with sinks must be secured in place.
Materials	Worktop material acid- and chemical-resistant solid laminate (T2). Other options are also available; read more on the Worktop materials page. Frame is powder-coated steel, designed to meet environment requirements in laboratory
Colour	White as standard, other colours available on request
Load capacity	Recommended load capacity is 200 kg/desk, providing sufficient rigidity to minimize sway and prevent surface deflection. Maximum load capacity 400 kg/desk, must not be exceeded. Higher load capacities also available; see, e.g., Heavy-duty tables or contact our specialists for further information.
Casters	Can be equipped with casters (four turning, of which two can be locked)
On request	Can be equipped with a full size lower shelf made of P5-class chipboard with a high-pressure laminate surface

VISU KALUSTE OY

Eeliksentie 6, 34870 Visuvesi, Finland

visu@visu.fi

+358 44 749 4940

visu.fi