
INNOSTAVIA YMPÄRISTÖJÄ
TIETEELLE JA TUTKIMUKSELLE

VISU Pro Standard 3

For acids, strong chemicals and equipment



The VISU Pro Standard 3 fume cupboard is specifically designed for acids, strong chemicals and equipment. The ceramic work-top provides excellent chemical resistance. The VISU Pro Standard 3 fume cupboard allows you to handle various health-hazardous substances safely while working with equipment.

VISU Pro Standard fume cupboards are available for fast delivery. Products are in stock with interim sales reservations. Contact our experts for more information!

Looking for something tailored specifically to your needs? VISU Pro fume cupboards are also available as fully customizable solutions.

VISU Pro fume cupboard

VISU Pro Standard 3 is known for:

- **High quality** – The VISU Pro Standard 3 fume cupboard is manufactured from high-quality, professional-grade materials. Its refined construction ensures a reliable, well-functioning unit without any compromises in the quality. All VISU's fume cupboards are designed to withstand decades of use, and the VISU Pro Standard 3 is nearly maintenance-free throughout its entire service life.
- **Ergonomic** – The clear and optimally designed details of the VISU Pro Standard 3 fume cupboard, together with the control buttons and service valves located on the front panel, support an ergonomic working posture.
- **Space saving** – The VISU Pro Standard 3 fume cupboard offers a space-saving solution. VISU Pro fume cupboards have the largest internal volume relative to their external dimensions in our product range.
- **Safe** – The VISU Pro Standard 3 fume cupboard emphases user safety. Extraction operates both from the work surface level and from the upper part of the work area across the full width of the fume cupboard. Additionally, the structure is easy to clean.
- **Ecological** – All VISU fume cupboards are responsibly designed and manufactured in Finland.

The fume cupboard can be equipped with optional features, such as electric height adjustment. Details provided below in bold

Product information

Standard widths	1200, 1500 and 1800 mm
Worktop depth	600 and 800 mm

VISU KALUSTE OY
Eeliksentie 6, 34870 Visuvesi, Finland
visu@visu.fi
+358 44 749 4940
visu.fi

INNOSTAVIA YMPÄRISTÖJÄ
TIETEELLE JA TUTKIMUKSELLE

Total depth	730 and 930 mm
Total height	2680 mm when 1-part sash totally opened **(2780 mm with electric height adjustment when 1-part sash totally opened)**
Worktop height adjustment	Manual 750–900 mm, set to 900 mm **Electric 750-1000 mm (on request)**
Worktop material	Ceramic
Side walls and back panel material	Polypropylene
Front sash	Vertical laminated glass
Frame	Powder coated steel
Ductwork	High-pressure laminate + back panel material
Standards	According to SFS-EN 14175-2: 2003 safety features: lift limiter in the front sash, set to 500 mm; sash emergency brake
Sockets	IP44, 2-socket outlet, 1 pc
Air flow control	0-1 control switch for ventilation (building services)
Tap (on request)	**Compressed air (CA) tap, control valve in front panel**
Residual current device	Included

Additional technical information

The technical properties depend on the fume cupboard width.

Widths, [mm]	**1200**	**1500**	**1800**	
Internal work area widths [mm]	1130	1430	1730	
Air volume [l/s]	170	215	260	Sash opened 300 mm, 0.5 m/s inflow, pressure drop 100 Pa
Standard lights LED [W]	18	24	30	LUX: 1022, CRI: 80, frequency: 3.3 kHz, colour temperature: 4000 K
Ventilation connection [mm]	200	250	2 x 200 (ctc 900 mm)	

Delivery and installation

Fume cupboards are delivered, if so agreed, installed in place, ready to be connected to building services systems. A fume cupboard must be connected to a separate exhaust air duct. The water supply, drainage, gas and electricity work must be performed by professionals.

VISU KALUSTE OY
Eeliksentie 6, 34870 Visuvesi, Finland
visu@visu.fi
+358 44 749 4940
visu.fi

INNOSTAVIA YMPÄRISTÖJÄ
TIETEELLE JA TUTKIMUKSELLE



VISU KALUSTE OY

Eeliksentie 6, 34870 Visuvesi, Finland

visu@visu.fi

+358 44 749 4940

visu.fi