

Equipment Stand

- With the Equipment Stand, you can elevate a device to an ergonomic working height.
- The top material is acid- and chemical-resistant solid laminate (T2). Other
 options are also available; read more on the <u>Worktop materials</u> page.
- The streamlined design ensures easy cleanability.
- Our standard solutions feature the most commonly used dimensions.
- Custom solutions are always tailored to the customer's needs.



Standard

Description	Product code	Standard dimensions [mm]			Additional information
		Width	Depth	Height	
Equipment Stand	RJ-T2	300-1200*	600, 800	280	Adjustable pads
Equipment Stand, with castors	RJp-T2	300-1200*	600, 800	280	On castors

^{*} Widths available in 100 mm increments.

Custom

In addition to standard models, we also manufacture equipment stands according to customer specifications. In custom solutions, dimensions, materials, and features are entirely up to the customer.

Feel free to ask our experts for more information, and let's design the right solutions together!

Additional information

Installation method Free-standing on the floor, with adjustable pads or castors (4 turning, of which 2 can be locked).

VISU KALUSTE OY

- Eeliksentie 6, 34870 Visuvesi, Finland
- @ visu@visu.fi
- **\(+358 44 749 4940**
- visu.fi



Materials	The top material is acid- and chemical-resistant solid laminate (T2). Other options are also available; read more on the <u>Worktop materials</u> page. The frame is powder-coated steel, designed to meet laboratory environment requirements.
Colour	White as standard, other colours available on request.
Load capacity	Recommended load capacity is 200 kg, providing sufficient rigidity to minimize sway and prevent surface deflection. The maximum load capacity is 400 kg, which must not be exceeded.

VISU KALUSTE OY

- eliksentie 6, 34870 Visuvesi, Finland
- visu@visu.fi
- **\(\sigma +358 44 749 4940 \)**
- visu.fi