

Spray booth

- Spray booth for educational environments
- The spray booth is designed for safe working with spray paints and fixatives
- Standard features include a replaceable filter fabric and a rotating painting stand
- A lockable base cabinet provides storage space for paints and other supplies
- The painting cabinet is also available with LED lighting



Product information

Standard width [mm]	800, 1000, 1200
Worktop depth [mm]	540
Overall depth [mm]	620
Overall height [mm]	2100
Height adjustment	Manual 750-900 mm
Clear working opening height [mm]	870
Worktop material	Acid-proof stainless steel
Side and rear panel materials	Powder-coated aluminum Rear panel is equipped with a replaceable paint filter
Internal features	Rotating panting turntable
Base cabinets	Cabinet manufactured from high-pressure laminate-faced P5-grade particleboard Lock Abloy Classic
Accessories	Available with LED lighting or ATEX-rated lighting options

VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi



INNOSTAVIA YMPÄRISTÖJÄ
TIETEELLE JA TUTKIMUKSELLE

Technical Information

Technical properties based on the width of the spray booth.

Standard width [mm]	800	1000	1200	
Airflow rate [l/s]	360	450	540	Filter face velocity: 0,5 m/s
Airflow rate [l/s]	180	225	270	Filter face velocity in educational environments: 0,25 m/s
Ventilation connection [mm]	250	250	250	

VISU KALUSTE OY

 Eeliksentie 6, 34870 Visuvesi, Finland

 visu@visu.fi

 +358 44 749 4940

 visu.fi